



A problem has occurred

2026-05-31 02:27:37

Error message:

This license has expired on 2026-05-30.

License Information:

License serial no:	3916
Licensee:	Adeona Oy
Product:	PDFReactor Web Service
Version:	12.0
License Type:	CPU
Amount:	12 Thread(s)
Maintenance Exp. Date:	2026-05-30
Expiration Date:	2026-05-30
Purchase Date:	2015-11-18
Conditions:	[This license is for use on development systems only. It may not be used on staging or productive systems of any kind.]
Sign Date:	2025-06-02 15:12

FRHF-EMC / BFSI-EMC

Kuparivoimakaapeli-EMC-FRHF

0,6/1 (1,2) kV



Palossa toimiva EMC voimakaapeli kiinteään sisä- ja ulkoasennukseen. Voidaan asentaa suoraan maahan. EMC-suojattu kaapeli tarjoaa erinomaisen suojan sähkömagneettisia häiriöitä vastaan. Kohteisiin, joissa turvallisuus edellyttää hälytys-, ohjaus-, merkinanto- ja energiasyöttöjärjestelmien toimintaa myös tulipalon aikana. Johdineriste on suojattava UV-säteilyltä. Asennus on tehtävä kansallisten asetusten ja määräysten mukaisesti. Kaapeli ei kuulu CPR luokituksen piiriin.

Lisätietoja	IEC 60331-21 Palossa toimiva, 180 min. IEC 60331-1, -2 EN 50200, EN 50362 Palossa toimiva, iskupoltto, 90 min. EN/IEC 60332-3-22 Nippuna paloa levittämätön, Katogoria A EN/IEC 61034 Vähäinen savun muodostus EN/IEC 60754 Halogeeniton, ei syövyttävä EN 50289-1-6 Sähkömagneettinen suorituskyky
Standardit	SFS 5547, HD 604 5 D
Johdin	Pyöreä kupariköysi, EN/IEC 60228 luokka 2
Eriste	Ristisilloitettu polyeteeni PEX ja mica-nauha
Johtimien tunnistaminen	Ruskea, musta, harmaa
Ulkovaippa	UV-suojattu polyolefiinisekoite, Oranssi
Tuotekoodi	1146646
Tuotteen koko	3x16/16
Kaapelin nimellishalkaisija mm	22
Kaapelin nimellispaino kg/km	1026
Asennuksen aikana, kaapeli cm	27
Lopullisessa asennuksessa, kaapeli cm	19
Maksimi DC resistanssi, johdin 20 °C Ω/km	1,15
Max. johdinlämpötila käytössä °C	90
Max. johdinlämpötila, oikosulku max. 5 s °C	250
Min. kaapelin käsittelylämpötila °C	-15
Vakiopakkaus m	Kela 500



REALOBJECTS

PDFReactor®

Evaluation Version

This PDF document was created by an evaluation version of RealObjects PDFReactor 12.3.2 (17644). The evaluation version is fully functional, but includes this information page. It must not be used for production purposes. The information page and all other evaluation notices must not be removed from the PDF file.

NOTE: Conversions in evaluation mode might be slower and the results might have a larger file size than in production mode.

Buy PDFReactor

To buy a PDFReactor license follow this link:

[Buy PDFReactor online](#)

About PDFReactor

RealObjects PDFReactor is a powerful formatting processor for converting HTML and XML documents into PDF. It uses Cascading Style Sheets (CSS) to define page layout and styles. The server-side tool enables a great variety of applications in the fields of ERP, eCommerce and Electronic Publishing.

PDFReactor supports HTML5, CSS3 and JavaScript.

It allows you to dynamically generate PDF documents such as invoices, delivery notes and shipping documents on-the-fly. PDFReactor allows you to easily add server-based PDF generation functionality to your application or service. Since PDFReactor runs on a server, the end-user in general does not need any software other than a PDF viewer.

For more information visit www.pdfreactor.com